

The Vollara Air & Surface Pro reduced 99.96% of airborne SARS-CoV-2, the virus responsible for COVID-19, within 1 minute.¹

This unaffiliated lab test was done on the lowest setting using only the ActivePure® Technology.

THE TECHNOLOGY

The Vollara® Air & Surface Pro combines multiple complementary technologies, including HEPA, activated carbon, and ActivePure® Technology. Patented ActivePure Technology is an advanced surface and air purification technology. It has been proven to reduce over 99.9% of many common airborne and surface contaminants (list of tested pathogens can be found in "The Proof" section below).

ActivePure Technology does not replace the need to follow public health guidelines and should be used as complementary technology.

THE PROOF

In extensive unaffiliated lab testing, ActivePure® Technology has been proven to significantly reduce the following contaminants and pathogens¹:

- SARS-CoV-2
- Staphylococcus aureus
- Aspergillus niger endospores
- H1N1 Influenza
- H5N8 Influenza
- MRSA
- Bacillus globigii
- MS2 Bacteriophage
- Staphylococcus epidermidis
- PhiX-174

- Erwinia herbicola
- Listeria monocytogenes
- Murine Norovirus
- E. coli
- · Candida auris
- Botrytis cinerea
- Sclerotinia sclerotiorum
- Legionella pneumophila
- Aspergillus versicolorClostridium difficile
- Salmonella enterica

THE BENEFITS

The Vollara Air & Surface Pro provides 24/7 surface decontamination and air purification. It is an proactive and effective solution for your home or business.

- Portable, lightweight device
- No installation plug-and-play solution
- · Easy to use and low maintenance
- Proven effective against many common viruses, bacteria, molds, and fungi¹
- Reduces smoke, allergens, odors, and VOC gases without the use of ozone
- Multiple carbon brushes aid in the capture of contaminants



¹View test results at Vollara.com/scientific-proof







Inducted into the 2017 Space Technology
Hall of Fame by the Space Foundation





	9940062 (ozone-free) Model: A1040B	FAMILY DURING USE PHASE DOES NOT EXCEED 0.005	
Product Information	Meets California Ozone Emissions Limit. CARB Certified.	PPM AS TESTED BY UL 867 UL.COM/ECV	
	Validated to UL 2998		
	ActivePure® Technology – (2) 6" Cells		
	HEPA Filter Screen		
Technology Included	Activated Carbon Filter		
	Carbon Brushes		
	Input Voltage: 100 ~ 240 VAC; 50/60 Hz		
Electrical	External Power Supply: DC 24 Volts; 1.5 Amps Max.		
	Power Consumption: 43 Watts Max.		
Mechanical	Nominal Airflow Rate: 40-60 CFM; Adjustable Fan Speed		
Safety	Conforms to UL 867		
Weight & Dimensions	7.6 lbs (3.5 kg)		
Weight & Dimensions	11.75" H x 9.5" W x 10" D (29.8 cm x 24.1 cm x 25.4 cm)		
Operating Temperature	34°F – 100°F (1°C – 38°C)		
Sound Level	45 dB(A) (on low); 55 dB(A) (on high)		
	Up to 2,000 sq. ft. (185 m²) depending on occupant density and other factors	5.	
Coverage ¹	High density commercial not to exceed 500 sq. ft. (46 m²).		
Warranty	Limited 3 year warranty		



	Contact Name:
<u></u>	Email:

	Phone Number:	
o J		

^{1.} Assumes 8 foot ceilings. Solutions should be customized based upon a variety of factors including HVAC system capabilities and settings, air flows taking into account walls, air pressure, and doors, ambient air temperatures and humidities, variable density, known VOC concentrations, other layers of protection.